


BECKER™ RIGID ALUMINUM FRAMES



Becker Rigid Aluminium Frames

Model	Profile Thickness	Wall Thickness	Recommended Max O.D. Length
1	1/2" x 1"	0.125"	18"
2	3/4" x 3/4"	0.125"	18"-24"
3	3/4" x 1 1/2"	0.125"	31"-36"
4	1" x 1"	0.070"	18"-24"
5	1" x 1"	0.125"	24"-30"
6	1" x 1 1/2"	0.125"	30"-36"
7	1" x 2"	0.125"	40"-45"
8	1 1/4" x 1 1/4"	0.095"	26"-30"
9	1 1/4" x 1 1/4"	0.125"	30"-35"
10	1 1/2" x 1 1/2"	0.070"	31"-36"
11	1 1/2" x 1 1/2"	0.095"	36"-40"
12	1 1/2" x 1 1/2"	0.125"	40"-50"
13	1 1/2" x 2"	0.125"	50"-55"
14	1 1/2" x 2 1/2"	0.125"	55"-75"
15	1 1/2" x 3"	0.125"	90"-105"
16	1 1/2" x 4"	0.125"	120"-140"
17	1 3/4" x 5"	0.125"	200" and up
18	2" x 2"	0.125"	60"-70"
19	2" x 3"	0.125"	70"-80"
20	2" x 4"	0.125"	140"-160"
21	2" x 6"	0.125"	240" and up

Custom-made to your exact requirements, these quality welded metal frames are much stronger than inferior wood frames, yet are conveniently lightweight and are more corrosion resistant when compared with steel. They are constructed with a surface ground or sandblast finish for excellent adhesion. Choose from a variety of profiles as well as wall thicknesses to meet strength requirements.