

Remove PW3

Low VOC Press Wash for Plastisol and UV-Cured Inks

Applications

Removes ink from screen with on press.

Characteristics

- Recommended for use with Plastisol and UV-Cured inks
- High flash point of 66°C

Features/Benefits

- Low VOC <500g/L

Directions For Use

Spray or wipe on both sides of the screen to open dried or clogged ink. Let evaporate and continue printing.

Health & Safety

Before using, refer to appropriate Safety Data Sheets. Contact SAATI at info.US@saati.com to request SDS.

Storage

When sealed in the original container and stored in cool conditions, SAATI chemical products will maintain their original properties for one year from the date of production.

Packaging

Available in 0.75 and 20 kilogram containers.

In North America available in one quart and in one, five, and fifty-five US gallon containers.



Warranty And Limited Warranty

The directions, recommendations and specifications contained within this Technical Data Sheet are meant as a guide for the use of the product and shall not bind the company. Product specifications are subject to change without notice.

The following is made in lieu of all other express or implied warranties, including any implied warranty of merchantability or fitness for a particular purpose; All SAATI manufactured liquid products are warranted to be free of defects in materials and manufacture and to meet the specifications in SAATI Product Bulletin.

SAATI will replace or refund the price of any SAATI manufactured liquid product that does not meet this warranty within the applicable warranty period.

The remedies are exclusive. In no case shall SAATI be liable for any other direct or indirect damage or loss, including without limitation any incidental, special or consequential damages, or any material costs or labor charges incident to the removal or replacement of any mesh, screen, ink, substrate, finished graphic or other item.